



NUSTRI

MADE IN ITALY



Ironing machines for knitwear factories, laundries and clothes factories



BURNER NOT INCLUDED



MOD. NS / 100

Steam generator with water space and horizontal water pipes. Boiler It **53,4** . Prearranged for the connection to blowed burner upright assembled. The machine is placed on an inox steel foot-board.



www.nustri.com



nustri@nustri.com



0039 055-8734007



0039 055-8735123



Ironing machines for knitwear factories, laundries and clothes factories

TECHINCALS CHARACTERISTICS	MOD.	NS 100
BOILER	Lt.	53.4
ELECTROPUMP Volts. 220 Hp. 1	Kwatt.	0,75
SAFETY VALVE	Ø	1 ¼"
INOX STEEL WATER CONTAINER	Lt.	70
BOILER CALORIES	Kcal./h	65.000 ****
MAXIMUM STEAM PRODUCTION	Kg/h	100
BOILER DISCHARGE	Ø	1"
SMOKES PIPE DISCHARGE	mm.	140
DOUBLE BLOWING STAGE <i>-NOT INCLUDED ***</i>	Trade mark	RIELLO UNIGAS
STEAM PRESSURE	bar	5,5
WATER INLET	Ø	1/2"
BACK-CONDENSE CONNECTION	Ø	1/2"
MAXIMUM LEVEL WATER OUTLET (for inox steel container)	Ø	1"
GAS INLET (it may be different)	Ø	½"
WATER CONSUMPTION - MAX	Lt./h.	50
DIESEL OIL CONSUMPTION - MAX	Lt./h	5,4 **
METHANE CONSUMPTION - MAX	M³/h	7 **
GAS/GPL CONSUMPTION- MAX	Kg./h	5,8 **
STEAM OUTLET	Ø	½"
MAXIMUM TOTAL POWER	Kwatt.	1
ELECTRIC FEED	Volts.	220 *
TENSION	Hz.	50 *
NET WEIGHT (without burner)	Kg.	110
DIMENSIONS H x L x D (without burner)	Cm.	110 x 75 x 60
* Different technicals characteristics are available on demand.		
** Specify the kind of fuel on order		
*** The burner is not included.		
Please ask our company for details .		
**** Boiler with <u>I.S.P.E.S.L. EXEMPTION</u> Ratified under 30.000 Kcal/h.		

Complete of :

- ◆ Boiler lt 53,4
- ◆ Feeler control level
- ◆ Glass gauge for water level
- ◆ Electric pump
- ◆ Cock for boiler discharge
- ◆ Cock for steam exit
- ◆ Connection for flue exit

Encombrance

