



NUSTRI

MADE IN ITALY



Ironing machines for knitwear factories, laundries and clothes factories



BURNER NOT INCLUDED

MOD. NS/150

Steam generator with horizontal water hoses and incorporated boiler It 57,2. Arranged for the connection with vertical blowed burner . The machine is assembled on inox steel surface. **Burner is not included.**



www.nustri.com



nustri@nustri.com



0039 055-8734007



0039 055-8735123



Ironing machines for knitwear factories, laundries and clothes factories

TECHNICALS CHARACTERISTICS	MOD.	NS 150
BOILER	Lt.	57.2
ELECTROPUMP Volts. 220 Hp. 1	Kwatt.	0,75
SAFETY VALVE	Ø	1 ½"
INOX STEEL WATER CONTAINER	-	<u>NOT INCLU- DED</u>
BOILER CALORIES	Kcal./h	97.000 ****
MAXIMUM STEAM PRODUCTION	Kg/h	150
BOILER DISCHARGE	Ø	1"
SMOKES PIPE DISCHARGE	mm.	160
DOUBLE BLOWING STAGE <u>-NOT INCLUDED</u> ***	Marca	RIELLO UNIGAS
STEAM PRESSURE	bar	5
WATER INLET	Ø	3/8"
WATER CONSUMPTION - MAX	Lt./h.	150
DIESEL OIL CONSUMPTION - MAX	Lt./h	6,5 **
METHANE CONSUMPTION - MAX	M³/h	7 **
GAS - GPL CONSUMPTION - MAX	Kg./h	7,7 **
STEAM OUTLET	Ø	3/4"
MAXIMUM TOTAL POWER	Kwatt.	1
ELECTRIC FEED	Volts.	220 *
TENSION	Hz.	50 *
NET WEIGHT (without burner)	Kg.	460
DIMENSIONS H x L x D (senza bruciatore)	Cm.	160 x 70 x 100
* Different technicals characteristics are available on demand.		
** Specify the kind of fuel on order .		
*** The burner is not included. Please ask our company for details .		
**** Boiler with <u>I.S.P.E.S.L. EXEMPTION</u> Ratified under 30.000 Kcal/h.		

Complete of

- ◆ Water hoses boiler It 57,2
- ◆ Feeler control level
- ◆ Electropump for water supply
- ◆ Tap for boiler discharge
- ◆ Tap for steam exit
- ◆ Connection for flue exit

Encombrance

