



NUSTRI

MADE IN ITALY



Ironing machines for knitwear factories, laundries and clothes factories



BURNER NOT INCLUDED

MOD. NS/250

Steam generator with horizontal water pipes and incorporated boiler **lt 61,8**. Arranged for the connection with vertical blowed burner . The machine is assembled on inox steel foot-board. **Burner is not included.**



Ironing machines for knitwear factories, laundries and clothes factories

TECHNICALS CHARACTERISTICS	MOD.	NS 250
BOILER	Lt.	61,8
WATER ELECTRIC PUMP Volts. 220 Hp. 1	Kwatt.	0,75
SAFETY VALVE	Ø	1 ½"
WATER TANK IN INOX STEEL	-	<u>NOT INCLU- DED</u>
BOILER CALORIES	Kcal./h	162.000 ****
MAXIMUM STEAM PRODUCTION	Kg/h	250
BOILER DISCHARGE	Ø	1"
PIPE SMOKES DISCHARGE	mm.	180
DOUBLE BLOWING STAGE BURNER - NOT INCLUDED ***	Brand	RIELLO UNIGAS
STEAM PRESSURE	bar	4,7
WATER INLET	Ø	3/8"
MAXIMUM WATER CONSUMPTION	Lt./h.	250
MAXIMUM DIESEL-OIL CONSUMPTION	Lt./h	16 **
MAXIMUM GAS METHANE CONSUMPTION	M³/h	19 **
MAXIMUM GPL CONSUMPTION	Kg./h	13 **
STEAM EXIT	Ø	3/4"
MAXIMUM TOTAL POWER	Kwatt.	1
ELECTRIC FEED	Volts.	220 *
TENSION	Hz.	50 *
NET WEIGHT (without burner)	Kg.	500
DIMENSIONS H x L x D (without burner)	Cm.	170 x 70 x 100
* Different technicals characteristics are available on demand.		
** Specify the kind of fuel on order		
*** The burner is not included. Please ask our company for details .		
**** Boiler with <u>I.S.P.E.S.L. EXEMPTION.</u>		

Complete of

- ◆ Water hoses boiler It 61,8
- ◆ Feeler control level
- ◆ Electric-pump for water supply
- ◆ Cock for boiler discharge
- ◆ Cock for steam exit
- ◆ Connection for flue exit

Encombrance

