



NUSTRI

MADE IN ITALY



Ironing machines for knitwear factories, laundries and clothes factories



BURNER NOT INCLUDED



MOD. NS / 50

Steam generator with space for water and horizontal water pipes. Boiler It **53,4** . Prearranged for the connection to blowed burner upright assembled. The machine is placed on an inox steel foot-board.



www.nustri.com



nustri@nustri.com



0039 055-8734007



0039 055-8735123



Ironing machines for knitwear factories, laundries and clothes factories

| TECHINCALS CHARACTERISTICS | MOD. | NS 50 |
|---|-------------------|------------------|
| BOILER | Lt. | 53.4 |
| ELECTROPUMP Volts. 220 Hp. 1 | Kwatt. | 0,75 |
| SAFETY VALVE | Ø | 1 ¼" |
| INOX STEEL WATER CONTAINER | Lt. | 70 |
| BOILER CALORIES | Kcal./h | 29.000 **** |
| MAXIMUM STEAM PRODUCTION | Kg/h | 50 |
| BOILER DISCHARGE | Ø | 1" |
| SMOKE PIPE DISCHARGE | mm. | 140 |
| DOUBLE BLOWING STAGE -NOT INCLUDED*** | Trade-mark | RIELLO UNIGAS |
| STEAM PRESSURE | bar | 5,5 |
| WATER INLET | Ø | 1/2" |
| BACK-CONDENSE CONNECTION | Ø | 1/2" |
| MAXIMUM LEVEL WATER OUTLET (for inox steel container) | Ø | 1" |
| WATER CONSUMPTION - MAX | Lt./h. | 50 |
| DIESEL OIL CONSUMPTION - MAX | Lt./h | 2,9 ** |
| METHANE CONSUMPTION - MAX | M ³ /h | 3,5 ** |
| GAS-GPL CONSUMPTION - MAX | Kg./h | 2,7 ** |
| STEAM OUTLET | Ø | ½" |
| MAXIMUM TOTAL POWER | Kwatt. | 1 |
| ELECTRIC FEED | Volts. | 220 * |
| TENSION | Hz. | 50 * |
| NET WEIGHT (without burner) | Kg. | 110 |
| DIMENSIONS H x L x D (without burner) | Cm. | 110 x 75 x 60 |
| * Different technicals characteristics are available on demand. | | |
| ** Specify the kind of fuel on order | | |
| *** The burner is not included. Please ask our company for details . | | |
| **** Boiler with <u>I.S.P.E.S.L. EXEMPTION</u> Ratified under 30.000 Kcal/h. | | |

Complete of :

- ◆ Boiler lt 53,4
- ◆ Feeler control level
- ◆ Glass gauge for water level
- ◆ Electric pump
- ◆ Cock for boiler discharge
- ◆ Cock for steam exit
- ◆ Connection for flue exit

Encombrance

